BX1822D

Overview

- 3.3 **Cubic Feet**
- 17.5"**across X 22.5 deep**
- **Double Wall construction**
- **Kanthal A-1 Elements**
- 208 **or 204 Volts**
- 40 **Amp Breaker Required**
- **Bartlett Controller**
- **CSA approved**

Product Description

This kiln is an excellent choice for the home studio or school. It is a double insulated kiln with 2 ½" of premium firebrick plus 1" of block insulation. This double wall insulation ensures a safer, cooler jacket and approximately 30% energy savings over single wall kilns.
The heavy-duty Kanthal A-1 elements are standard along with a floor element for more even firings.
The jacket and fittings are all stainless steel or corrosion resistant metal.
The BX1822D is equipped with the Bartlett V6 2 Zone electronic controller which is mounted on an angled easy view control panel. The extra zone control comes standard at NO EXTRA CHARGE for excellent temperature control.
The Tucker's Cone Art BX1822D sets the standard for excellence in quality construction and reliability. Please request information on the MX1822D which is equipped with a kiln sitter and timer.

Furniture Kit

- **Three 15.5" dia. full shelves**
- **One 15.5" dia. half shelf**
- **Three each of 1 3/4" square X 1",2",4",6" posts**
- **Two kilograms kiln wash**
- **All shelves and posts are high alumina,rated for cone 11.**

Specifications

PHASE	VOLT	INSIDE DIMENSIONS	OUTSIDE DIMENSIONS	SECTIONS	CUBIC FEET	AMPS	BREAKER REQUIRED	CU WIRE GA(AWG)	KILOWATTS	SHIP WT LBS	MAX CONE	MAX TEMP
1	240	22.5 x 17.5	24.5 x 27.5	3	3.30	28.00	40A	0	6.70	240.00	10	
1	208	22.5 x 17.5	24.5 x 27.5	3	3.30	32.00	40A	0	6.70	240.00	10	