

## GTS 2541 Specific Content

### Usage Guidelines:

- Primary images are included and are to be used as main image for the product.
- Primary images can be resized. For primary images, the white space around product can be cropped, but the image must but not be cut-off by cropping. For alternative images, suggested cropping to highlight a specific region of the kiln or oven may have already been prepared for use.
- If alternate images are included, then they are to be used as complimentary images for the product, but not as a primary image.
- Copy can be resized but not combined into a larger paragraph. If text is separated by paragraphs, please separate each paragraph as shown within the Product Specific Content.
- Whenever possible, features and options should be included in list form and not in paragraph form and using commas to separate each specific feature or option.
- Evenheat has the right to edit these guidelines in a manner that will assist brand consistency throughout the industry.

### GTS 2541 Images



Primary image (150 ppi,3.75in x 3.75in)

[PNG \(bitmap\)](#)

### Copy - GTS 2541 Tagline

The Original Leads the Way

### Copy - GTS 2541 Teaser Information

GTS 2541  
240V Studio Kiln  
Rampmaster Control  
Large 25" L x 41" W Design  
Available in 9" x 13.5" Depths

### Copy - GTS 2541 Description

Evenheat's GTS 2541 is the original large, oval shaped kiln that continues to lead the way in performance and design.

The GTS 2541 features our exclusive Rampmaster w/ Express Mode Control, Swing View Adjustable Viewing, Wide Lid Handle and Full Stainless Jackets. Add our Patented Dyna-Lift lid assist and viewing windows to your GTS 2541 for the ultimate in glass kiln performance.

### Copy - GTS 2541 Features

- Rampmaster w/ Express Mode
- Swing View Adjustable Control
- Wide Lid Handle
- Full Stainless Jacket
- Corner Mounting Technique
- Properly Sized Stands

- 3 Position Lid Vent
- Large Size
- Responsive Thermocouples
- Lid Security Bar
- Top and Side Fire Configuration
- Excellent Temperature Distribution

### **Copy - GTS 2541 Options**

- Dyna-Lift Lid Lift Assist
- Viewing Window
- Depth Options
- Lid Power Interrupt Switch
- 16" Tall Stand
- Vent System
- PC Software and Hardware
- Voltage and Phase Options

### **Copy - GTS 2541 Suitability**

The GTS 2541 is designed to fire glass and is quite capable of all glass related firing up to 1800°F (982°C), such as painting, fusing, slumping, casting, etc. It should be noted that the GTS 2541 is designed to fire a single layer or shelf. The nature of the GTS 2541 is to provide heat from the lid elements directly to the shelf containing the glass. Attempting to fire glass below the top shelf is likely to lead to frustration and disappointment.

While the GTS 2541 is designed exclusively for glass work it is possible to fire a variety of materials including metal clays, low fire ceramic, china paints and metals processing provided the firing temperatures do not exceed 1800°F.

### **Copy - GTS 2541 Specifications**

#### **9" Deep Model Chamber Size**

41" W x 25.25" L x 9" D - 4.8 cubic feet  
(104.1cm Wide x 64.1cm Long x 22.9cm Deep - 136L)

#### **13.5" Deep Model Chamber Size**

41" W x 25.25" L x 13.5" D - 7.2 cubic feet  
(104.1cm Wide x 64.1cm Long x 34.3cm Deep - 204L)

#### **North American Electrical Specifications**

Operating Voltage: 240V (208V and 3 phase available)  
Amperage: 40A  
Watts: 9600W  
Power Cord Plug Style: NEMA 6-50P

#### **Global Electrical Specifications**

Operating Voltage: 400V  
Amperage: 15.7A  
Watts: 10,800W

Maximum Usable Temperature: 1800°F (982°C)  
Ship Weight: 280lb (127kg)