

IMPORTANT NOTES FOR USE OF PLASTER TRAP

CONGRATULATIONS ON YOUR PURCHASE OF ONE OF THE FINEST, MOST ECONOMICAL PLASTER TRAPS ON THE MARKET. BY FOLLOWING THE ENCLOSED INSTRUCTIONS, YOU SHOULD RECEIVE MANY YEARS OF TROUBLE-FREE SERVICE FROM YOUR PLASTER TRAP. THANK YOU FOR YOUR PURCHASE.

1. THE PLASTER TRAP DOES NOT INCLUDE THE FITTINGS FOR ATTACHMENT TO YOUR SINK. THE FITTINGS REQUIRED ARE 1 1/2" SCHEDULE 40. WE INCLUDE THIS INFORMATION SHOULD YOU DECIDE TO INSTALL THE TRAP YOURSELF. THE FITTINGS ARE AVAILABLE AT YOUR LOCAL HARDWARE OR PLUMBING SUPPLY STORE. MANY PEOPLE USE FLEXIBLE CORRUGATED TUBING FOR INSTALLATION. THIS ALLOWS FOR EASIER INSTALLATION AND ALSO ALLOWS THE TRAP TO SIT ON THE FLOOR THEREBY REDUCING STRAIN ON YOUR PIPES. THIS IS THE TYPE OF INSTALLATION WE RECOMMEND.

2. THE TRAP LINERS (BAGS) FIT VERY SNUGLY AROUND THE RIM OF THE PAIL. WHEN INSTALLING A LINER IT IS VERY IMPORTANT TO REMOVE AS MANY WRINKLES AS POSSIBLE. WRINKLES ARE THE MAIN CAUSE OF MOST LEAKS. THE BEST WAY TO INSTALL A LINER IS TO FOLD OVER 4 1/2 " OF THE LINER ON THE OUTSIDE, THEREBY CREATING A "LIP". PLACE THE LINER IN THE PAIL AND PUSH DOWN ON THE BOTTOM. THE LIP GOES ON THE OUTSIDE OF THE PAIL. THE BOTTOM OF THE LINER SHOULD BE SUPPORTED BY THE BOTTOM OF THE PAIL. THE LINER IS LONG ENOUGH TO ALLOW THIS.

3. IT IS RECOMMENDED THAT THE LINERS ARE CHANGED FREQUENTLY DEPENDING ON THE AMOUNT OF USE. DO NOT ALLOW THE LINER TO FILL UP TO THE TOP WITH PLASTER. PLASTER SHOULD NOT BE CLOSER THAN 3-4 INCHES FROM THE TOP OF THE PAIL. IT IS RECOMMENDED TO THAT YOU DETERMINE THE APPROXIMATE TIME IT TAKES TO FILL YOUR LINER TO IDENTIFY AN ANTICIPATED REPLACEMENT SCHEDULE.

PLASTER TRAP INSTRUCTIONS

1. ATTACH THE SMALL HOSE TO THE SIPHON VALVE.
2. PLACE THE END OF HOSE IN A CONTAINER TO CATCH SIPHON RUN OFF. THE CONTAINER SHOULD BE AT LEAST 1 QUART CAPACITY.
3. OPEN BALL VALVE.
4. TURN ON WATER TO START SIPHON. TURN WATER OFF WHEN SIPHON STARTS.
5. CLOSE VALVE WHEN SIPHON STOPS.
6. LOOSEN 4 WING NUTS AND REMOVE PAIL FROM TOP.
7. CLOSE LINER WITH TIE BEFORE EMPTYING.
8. CARRY PAIL TO WASTE RECEPTACLE. CAREFULLY DISPOSE OF PLASTER FILLED LINER. IT IS RECOMMENDED THAT YOU KEEP THE LINER IN THE PAIL UNTIL YOU PLACE THE LINER IN THE TRASH. THIS WILL HELP TO AVOID SPILLS AND EXCESS STRAIN ON THE FILLED LINER.
9. PLACE NEW LINER IN PAIL WITH EXCESS PULLED OVER PAIL LIP. REATTACH TO TRAP TOP. YOUR TRAP IS NOW READY FOR USE.

