

SAFETY DATA SHEET

Section 1: IDENTIFICATION

Name, address, telephone number and emergency telephone number of the manufacturer:

Standard Ceramic Supply Company 24 Chestnut Street / P.O. Box 16240 Carnegie, PA 15106-2028

Telephone / Emergency Telephone Number: 412-276-6333

Product Identifier used on the label: Standard Moist and Dry Clays 112, 211, 225, 266, and 710

Recommended use of product: Ceramic ware

Section 2: HAZARDS IDENTIFICATION

Hazard classification of chemical: Miscellaneous

Hazard Statement(s): Contains silica dust.

Precautionary statement(s): Not harmful in moist form.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER	% OF FORMULA
1332-58-7	0% - 35%
68476-25-5	0% - 15%
1302-93-8	0% - 5%
1313-13-9	0% - 1%
1309-37-1	0% - 10%
14808-60-7	0% - 15%
7732-18-5	
	1332-58-7 68476-25-5 1302-93-8 1313-13-9 1309-37-1 14808-60-7



Section 4: FIRST-AID MEASURES

DESCRIPTION OF FIRST-AID MEASURES

Ingestion: Contact a physician immediately.

Inhalation: May cause irritation; remove from exposure.

Skin Contact: May cause irritation; rinse skin with soap and water.

Eye Contact: May cause irritation; flush eyes with water for at least 15 minutes. If irritation

continues afterwards, contact a physician.

Section 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Suitable extinguishing media: None

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Protective equipment for firefighters: None

Special firefighting procedures: None

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and/or Emergency Procedures: None

Environmental Precautions: None

Methods and Materials for Containment and Clean up: Clean up any wet spills or clay slop with a damp sponge. For dry spills, spray with water and use a damp sponge to clean up.

Special Spill Response Procedures: None

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling and Use: None

Conditions for Safe Storage: None

Incompatible Materials: None



Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS

OSHA PEL	ACGIH TLV
N/A	N/A
N/A	N/A
15mg/m3	10mg/m3
5mg/m3	0.2mg/m3
10mg/m3	5mg/m3
6mg/m3	3mg/m3
N/A	N/A
	N/A N/A 15mg/m3 5mg/m3 10mg/m3 6mg/m3

EXPOSURE CONTROLS

Ventilation and engineering measures: None

Respiratory protection: Use a NIOSH approved respirator.

Skin protection: Wear appropriate protective clothing such as overalls, smocks, and aprons.

Eye/face protection: None


Hygienic Practices: Food, beverages, and smoking materials should not be in work area. Employees should wash hands thoroughly before eating, drinking, or smoking.

Section 9: PHYSICAL/CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Solid

Upper/lower flammability or explosive limits: None

Odor: None





Vapor pressure: N/A

Odor threshold: Negligible

Vapor density: N/A

pH: N/A

Relative density: N/A

Freezing point: N/A

Solubility(ies) N/A

Initial boiling point and boiling range: N/A

Flash Point: N/A

Evaporation rate: N/A

Flammability (solid gas) N/A

Partition coefficient: n-octanol/water: None

Auto-ignition temperature: N/A

Decomposition temperature: None

Viscosity: N/A

Section 10 : STABILITY / REACTIVITY

Reactivity: N/A

Chemical stability: Stable

Possibility of hazardous reactions: None

Conditions to avoid: None

Incompatible materials: None

Hazardous decomposition products: N/A

Section 11: TOXICOLGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

Routes of Entry: Inhalation is the most important during excessive handling of clay.



POTENTIAL HEALTH EFFECTS, Signs and symptoms of short-term (acute) exposure:

Sign and symptoms inhalation: Coughing or irritation may occur.

Sign and symptoms ingestion: Sickness or irritation may occur.

Sign and symptoms skin: Redness or irritation may occur.

Sign and symptoms eyes: Redness or irritation may occur.

Potential chronic health effects: These mixtures contain silica, which can cause Silicosis through inhalation over an extended period of time. Overexposure to silica may also result in injury to the lungs.

Carcinogenicity: Silica (Quartz) is a human carcinogen.

Toxicological data: These products conform to 16 CFR 1500.14 (LHAMA) and ASTM-4236. They have been certified by an independent, 3rd party toxicologist to be NON-TOXIC.

Section 12: ECOLOGICAL INFORMATION (non-mandatory)

Eco toxicity: None

Persistence and degradability: Yes

Bioaccumulation potential: No

Mobility in soil: No

Other adverse environmental effects: None

Section 13: DISPOSAL CONSIDERATIONS (non-mandatory)

Handling for Disposal: None

Methods of Disposal: None

Section 14: TRANSPORT INFORMATION (non-mandatory)

UN Shipping Name: N/A

UN Number: N/A

-

Environmental Hazard: None

Packing Group: None

Page | 5



Transportation Hazard Class: N/A

Special Precautions: None

NOT DANGEROUS FOR TRANSPORT

Section 15: REGULATORY INFORMATION (non-mandatory)

Silica (Quartz) is listed by California, Proposition 65, as a carcinogen.

Silica (Quartz) is listed on the IARC, OSHA, and NTP carcinogen list.

All ingredients are on U.S. TSCA Inventory.

All products listed in this SDS conform to ASTM-4236 standards. Materials have been evaluated under the provisions of 16 CFR 1500.14 of the Labeling of Hazardous Art Material Act. These products have been listed as non-toxic and non-flammable under proposed use conditions. No specific warning is required.

Section 16: OTHER INFORMATION

This information is furnished with out warranty, representation, inducement or license or any kind, except that it is accurate to the best of knowledge of Standard Ceramic Supply Company or obtained from other references and sources believed to be accurate.

Standard Ceramic Supply Company does not assume any legal responsibility for use or reliance on our products. Customers are encouraged to conduct their own tests before using any product. Read all product labels prior to handling.

Preparation date: 05/22/2014